



Tie Offs

A convenient way to attach rope or web to trailer side wall.

Series E and A Rope Tie Off



Part No. 40386-10
3-piece end fitting for rope use with Series E or Series A Track
Breaking Strength Capacity: 3,000 lbs./1,363 kg.
Working Load Limit: 1,000 lbs./454 kg.
Weight: .30 lb./ .14 kg.

Series E and A Rope Tie Off



Part No. 40386-11
Spring actuated fitting for rope use with Series E or Series A Track
Breaking Strength Capacity: 3,000 lbs./1,363 kg.
Working Load Limit: 1,000 lbs./454 kg.
Weight: .40 lb./ .18 kg.

Series F Rope Tie Off



Part No. 40386-12
For rope use with Series F Track
Breaking Strength Capacity: 1,500 lbs./681 kg.
Working Load Limit: 500 lbs./227 kg.
Weight: .30 lb./ .14 kg.
Part No. 40386-13
For 1" hole diameter track (Canada)
Weight: .30 lb./ .14 kg.

Series E and A Fitting w/ D-Ring



Part No. 49542-10
Breaking Strength Capacity: 3,000 lbs./1,363 kg.
Working Load Limit: 1,000 lbs./454 kg.
Weight: .34 lb./ .15 kg.

Series E and A Articulated Track Fitting



Part No. 47772-12
Breaking Strength: 3,000 lbs./1,363 kg.
Working Load Limit: 1,000 lbs./454 kg.
Weight: .45 lb./ .20 kg.

Truck & Trailer Fittings

Ankra Pan Fittings are designed for low-profile mounting in trucks and trailers. The Recessed Pan Fitting is made for heavy-duty floor applications and has a tension feature that reduces ring movement while allowing easy lifting for access. The Stake Pocket Anchor can be surface or flush mounted for installing in trailer floors and accepts roll cart lock pins.



Part No. 45545-15
with black trim collar
Breaking Strength Capacity: 1,600 lbs./727 kg.
Working Load Limit: 530 lbs./240 kg.
Weight: .30 lb./ .14 kg.



Part No. 49371-10
Stake Pocket Anchor
Conforms to USPS drawing B-13956.
Black Lacquer Finish
Weight: 0.98 lb./ .44 kg.



Part No. 45849-13
Recessed Pan Fitting
Breaking Strength Capacity: 5,000 lbs./2,272 kg.
Working Load Limit: 1,666 lbs./757 kg.
Weight: 1.20 lbs./ .55 kg.


Door Pull Straps



Strength-tested Ankra door pulls provide ease in pulling overhead and side doors and wheel carts. Featuring a galvanized steel clip for rust protection and pre-punched holes for easy installation, door pulls come in 18", 24" and 36" lengths.

Part No. 49015-18 18-in. Door Pull Strap Weight: .20 lb./ .09 kg.
Part No. 49015-24 24-in. Door Pull Strap Weight: .30 lb./ .14 kg.
Part No. 49015-36 36-in. Door Pull Strap Weight: .40 lb./ .18 kg.

Transmat® Friction Mat



- Durable rebonded rubber
- Coefficient of friction of 1.0
- Tensile strength of 17.5 psi minimum
- Shore A Hardness of 40-60 points

Product No. 49382-10 Sheet 3' x 3' 2mm thick
Product No. 49382-11 Roll 3' x 1900' 2mm thick
Product No. 49382-12 1' x 5' 1/4" thick w/handholds

